



GENERAL CAR INFO		DIMENSIONS/CAPACITIES		SPECIALTY SUPPLIERS AND PART NUMBERS			
Built Date	2001-2002	Length Over Strikers	54' - 2 1/2"	Truck Type	ASF Super Service Ride Master	Draft Gear	N/A
Car Builder	Trinity Ind Plant 372	Length Over Couplers	58' - 6 1/2"	Bols. Patt./ AAR Code	B9A-YY4N-FX, Gr B+	Cushioning	ASF/Keystone, E-1372G-B
Builder Lot No.	2834	Cpld Length (Full Draft)	58' - 10 1/2"	Side Frame/AAR Code	F9A-11EN-UA, Gr B+	Yoke	ASF/Keystone YF-15-J
AFE Number		Truck Centers	40' - 10"	Truck Spring Group	7 D-5 O, 7 D-5 I, 2 D-6A II	Brake Control Valve	NYAB DB-60S
AAR Mech. Design.	XP	Inside Length	50' - 6"	Snubbing Type	ASF SS Ride Master	Portioning Valves	DB-10 / DB-20
AAR Car Code	A406	I W (Between Rub Rails)	N/A	Snubber Spring Group	ASF 5062 O, ASF 5063 I	Brake Cylinder	New York 10" X 12" ABU
GST Code	A6	I W (Between Side Sheets)	9' - 6"	Column Wear Plate	ASF 98-1-10232	Slack Adjuster	EII-Natl 2000-DJ
Clearance Plate	Exceeds Plate F	Inside Height	13' - 0"	Pedestal Roof Liners	Transdyne A05048	Brake Beam	Triax YSD #24 D-2531
C.G. - Empty	63"	Ext Width	10' - 8"	Wheels	36", 1W CH-36, Class C	Brake Beam Wear Pl	Zeftek ZT-1696-NH
C.G. - Loaded*	98"	Extreme Height	16'-10 5/8"	Axle	Trinity Grade F 6-1/2 X 9	Brake Shoes	RFP 2"
Min Curve-Cpl'd	210 ft.			Roller Bearing	Timken 6 1/2X9, AP-2	Handbrake	Universal 9300-3, 1993
Min Curve-Uncpl'd	150 ft.	Volume	6235 cu. ft.	Adapter	Hayes 6 1/2" X 9"	Floors (Mfg.)	Stanrail 70K Knurled Steel
Brake Ratio-Empty	25%	Gross Rail Load	286,000 lb	Truck Side Bearing	A. Stucki 688-BR	Doors (Mfg.)	YSD 12' Single Plug
Brake Ratio-Loaded	11%	Light Weight	74,000 lb	Horiz Center Plate Liner	Mn Sil	Lading Anchors	Ireco (120) Sngl 2761
Brake Ratio-H.B.	12%	Load Limit @ 286 K	212,000 lb	Vertical Wear Ring	Stainless Steel		40" Cont 3846 (12)
		Floor Rating	70K	Coupler/Knuckle	ASF SBE67DE/E50BE	Roof	Stanrail DR-12304
* 98" C.G. with lading Hgt - 11'-10" above floor.		Door Opening Width	12'-0"	Draft Sill / Striker Assy.	Built Up Welded	Load Dividers	N/A
		Door Opening Height	12'-4"	Front Draft Lug	Fabricated	Lining (Side)	N/A
		Floor Height (Light Car)	3'-7 7/8"	Rear Draft Lug	N/A	Lining (End)	N/A
FORMER REPORTING MARKS				Center Plate	ASF BS-341-E AAR M-201	Side Rubrails	N/A
				Coupler Carrier Wear Pl	Keystone P12692 Mn Steel	Floor Anchors	Snugger 72320/72115
				Uncoupling Device	Stanrail No. 586	Paint	Valspar WKB0023
NOTES AND EXCEPTIONS:							Interior Sigma 7456US-7003
BNSF 728300-728724 Center Sill material without copper content						Decals	Trinity Avery XL 1000
BNSF 728650-728774 Equipped W/NACO S-2-HD W/SCT Split Wedge							
BNSF 728775-728824 & 728941-728990 Equipped W/NACO S-2-HD W/Pennsy Split Wedge						Paint (First 14 C/S)	Davis-Frost WB CL-616
BNSF 728825-728840 & 728991-728994 Equipped W/NACO S-2-HD W/Pennsy Split Wedge, Adapter Plus And Non-Metallic Trainline							Interior Davis-Frost White WB DTM CL-612
BNSF 728850-728861 Equipped W/NACO S-2-E W/SCT Standard Wedge							
BNSF 728995-728999 Equipped W/StanRail Stainless Steel Roofs							